

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
7 February 2002 (07.02.2002)


PCT

(10) International Publication Number
WO 02/10029 A1

- (51) International Patent Classification⁷: **B65D 35/36** (71) Applicant (*for all designated States except US*): **PFIZER PRODUCTS INC.** [US/US]; Eastern Point Road, Groton, CT 06340 (US).
- (21) International Application Number: **PCT/US01/41306**
- (22) International Filing Date: **9 July 2001 (09.07.2001)** (72) Inventor; and (75) Inventor/Applicant (*for US only*): **KNIERIEMEN, Paul** [US/US]; 116 Pinehurst Avenue, New York, NY 10033 (US).
- (25) Filing Language: **English**
- (26) Publication Language: **English** (74) Agents: **RICHARDS, John et al.**; Ladas & Parry, 26 West 61st Street, New York, NY 10023 (US).
- (30) Priority Data:
60/221,641 28 July 2000 (28.07.2000) US (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK,
- (63) Related by continuation (CON) or continuation-in-part (CIP) to earlier application:
US 60/221,641 (CON)
Filed on 28 July 2000 (28.07.2000)

[Continued on next page]

(54) Title: **APPLICATOR**



(57) Abstract: An applicator (10) comprises a flexible container (14) having an upper end portion (16) with a dispensing orifice (18) therein. An applicator head (24) of foam material having a plurality of protrusions thereon is secured to an outside surface of the upper end portion. Substances (12) within the flexible container (14) flow through the foam material of the applicator head (24) to the exterior surface thereof when such substances (12) are dispensed through the orifice (18). The applicator (10) also has a removable closure cap (30), and releasable locking structure is provided on an inside surface of the closure cap (30) and an outside surface of the upper end portion of the flexible container (14) so that the closure cap (30) is releasably secured to the flexible container (14).

WO 02/10029 A1



SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.

(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published:

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

APPLICATORBackground of the Invention

The present invention relates to an applicator comprising a container and a closure cap, and more particularly to an applicator that dispenses and applies the substances within the container where desired.

Many consumer products are packaged in small hand held containers with removable closure caps to retain the freshness of the product between uses thereof. However, these container and closure cap assemblies are somewhat complicated in construction and in many instances they simply function to dispense the material within the container.

Summary of the Invention

Accordingly, it is an object of the present invention to provide an applicator which is simple in construction and simple to use.

Another object of the present invention is an applicator which functions to both dispense and apply the container contents where desired.

In accordance with the present invention, an applicator comprises a flexible container having an upper end portion with at least one dispensing orifice therein. An applicator head of foam material having a plurality of protrusions thereon is secured to the outside surface of the upper end portion of the flexible container whereby substances within the container flow through the foam material of the applicator head when dispensed through the orifice. A closure cap is removably snap fitted over the upper end portion of the container. Releasable locking structure is located on the inside surface of the closure cap and the outside surface of the upper end portion of the flexible container so that the closure cap is releasably secured to the flexible container.

The releasable locking structure preferably includes a plurality of spaced apart outwardly directed lugs on the upper end portion of the flexible container and a plurality of inwardly directed lugs on the inside surface of the closure cap that snap fit with the lugs on the flexible container. The closure cap preferably includes an oval shaped side wall. The upper end portion of the flexible container has a complimentary oval shape.

In a preferred embodiment of the present invention, the applicator head of foam material includes a plurality of raised protrusions equally spaced apart and arranged along

-2-

an oval path near the outer edge of the applicator head with several additional protrusions positioned within the oval path.

Brief Description of the Drawings

5 Novel features and advantages of the present invention in addition to those noted above will become apparent to persons of ordinary skill in the art from a reading of the following detailed description in conjunction with the accompanying drawings wherein similar reference characters refer to similar parts and in which:

10 Figure 1 is front elevational view of an applicator, according to the present invention, the rear elevational view being identical;

Figure 2 is a right side elevational view of the applicator shown in Figure 1, the left side elevational view being identical;

Figure 3 is a top plan view of the applicator shown in Figures 1 and 2,

Figure 4 is a bottom plan view of the applicator shown in Figures 1-3;

15 Figure 5 is a front elevational view of the applicator shown in Figures 1-4 with the closure cap removed, the rear elevational view being identical;

Figure 6 is a top plan view of the applicator with the closure cap removed;

Figure 7 is a right side elevational view of the applicator with the closure cap removed, the left side elevational view being identical;

20 Figure 8 is a bottom plan view of the closure cap shown in Figures 1-4;

Figure 9 is a partial front elevational view similar to Figure 1 but with portions broken away to show interior details; and

Figure 10 is a fragmental enlarged cross-sectional view showing details of the foam head of the applicator.

Detailed Description of the Invention

25 Referring in more particularity to the drawings, Figures 1-8 illustrate the exterior features of an applicator 10 for dispensing and applying materials or substances, such as ointments, creams and the like. Applicator 10 may be manufactured from any suitable thermoplastic material compatible with the substance packaged. Such thermoplastic materials include polyethylene and polypropylene, for example. Extrusion and welding techniques, well known in the art, may be used to produce the finished applicator product.

30

Applicator 10 comprises a flexible container 14 having an upper end portion 16. As shown best in Figure 9, dispensing orifice 18 is provided in the upper end portion 16 of the container. Alternatively, the dispensing orifice may be offset and/or more than one orifice may be used. The lower end of container 14 is closed by a straight seal 20.

5 The upper end portion 16 of applicator 10 includes an upwardly extending side wall 22, and an applicator head 24. Foam material and bearing a plurality of protrusions is secured within the upwardly extending side wall 22, as shown best in Figure 9. The foam material consists of closed cell foam, and the substance 12 flows through a passageway 40 in the foam to the exterior surface of the applicator head when the flexible container 14 is squeezed thereby dispensing the substance through the orifice 18 into the foam material. 10 Alternatively, the material of the applicator head may be selected so that the applicator head is impregnated with substance 12 when the container is squeezed.

 The upper surface of the applicator head includes a plurality of spaced apart bumps or protrusions 26, each having a height B of approximately 1/8 to 1/4 inches and a 15 circular base dimension having a radius A of 1/8 to 1/4 inches. As shown best in Figure 6, the dimples 26 are equally spaced apart and arranged along an oval path near the outer edge of the applicator head with several additional protrusions positioned within the oval path. Although twelve protrusions are shown, if the protrusions are larger, a lesser number may be sufficient. Also, if the protrusions are smaller, more protrusions may be 20 desirable.

 Applicator 10 also includes a flexible closure cap 30 having a generally flat top 32 and a downwardly extending surrounding side wall 34. Closure cap 30 snap fits over the upper end portion 16 of the flexible container to releasably secure the closure cap to the container. Releasable locking structure providing the snap fit is located on the inside of 25 the surrounding wall 34 and on the outside of the upper end portion 16. The locking structure on the inside of a surrounding wall 34 includes four equally spaced apart inwardly extending lugs 36, and the locking structure on the outside surface of the upper end portion 16 includes four equally spaced apart outwardly extending lugs 38 in vertical alignment with the lugs 36 on the closure cap.

30 In the preferred embodiment of the present invention, the surrounding wall 34 of the closure cap has an oval shape and the upper end portion of the flexible container has a

-4-

complimentary oval shape. Accordingly, whenever the closure cap is fitted over the upper end portion of the flexible container, the lugs 36 and 38 are always in vertical alignment with one another to produce the desired interference with one another which produces the snap fit.

5 In use, the closure cap is first removed from the upper end portion of the flexible container to expose the applicator head 24 of foam material. Container 14 is then gently squeezed to dispense substance 12 through orifice 18 into the foam material to the exterior surface thereof. The applicator head 24 is then rubbed over the desired area to stimulate that area and simultaneously apply substance 12. Upon completion of the
10 application process, the closure cap is returned and snap fitted over the upper end portion of the container to preserve the freshness of the packaged substance.

CLAIMS

1. An applicator comprising a flexible container and a closure cap, the flexible container having an upper end portion with at least one dispensing orifice therein, an applicator head of foam material having a plurality of protrusions thereon and being
5 secured to an outside surface of the upper end portion whereby substances within the flexible container flow through the foam material of the said applicator head when dispensed through the orifice, and releasable locking structure on an inside surface of the closure cap and an outside surface of the upper end portion of the flexible container whereby the closure cap is releasably secured to the flexible container.
- 10 2. An applicator as in claim 1, wherein the releasable locking structure includes a plurality of spaced apart outwardly directed lugs on the upper end portion of the flexible container and a plurality of inwardly directed annular lugs on the inside surface of the closure cap that snap fit with the lugs on the flexible container.
- 15 3. An applicator as in claim 1, wherein the closure cap includes an oval shaped side wall, and wherein the upper end portion of the flexible container has a complementary oval shape.
4. An applicator as in claim 1, wherein the dimpled applicator head of foam material includes a plurality of protrusions equally spaced apart and arranged along an oval path
20 near an outer edge of the applicator head with several additional protrusions positioned within the oval path.

FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 7




FIG. 6




FIG. 8




FIG. 9





FIG. 10



INTERNATIONAL SEARCH REPORT

PCT/US 01/41306

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 B65D35/36

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 7 B65D A45D A61M

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)
PAJ, EPO-Internal

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 3 121 906 A (DAVID HULSH SHELDON) 25 February 1964 (1964-02-25) figures	1
A	PATENT ABSTRACTS OF JAPAN vol. 1999, no. 13, 30 November 1999 (1999-11-30) & JP 11 221116 A (SHISEIDO CO LTD), 17 August 1999 (1999-08-17) abstract	1
A	US 2 118 051 A (MACMICHAEL HUGH R) 24 May 1938 (1938-05-24) page 1, line 27 - line 52; figures	1
A	DE 78 09 143 U (VER DEUTSCHE METALLWERKE AG) 6 July 1978 (1978-07-06) figures	1
-/--		

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

*** Special categories of cited documents :**

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *Z* document member of the same patent family

Date of the actual completion of the international search

15 January 2002

Date of mailing of the international search report

22/01/2002

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Fournier, J

INTERNATIONAL SEARCH REPORT

Intern. Application No
PCT/US 01/41306

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	EP 0 315 513 A (PLOT MICHEL MARCEL EUGENE) 10 May 1989 (1989-05-10) column 3, line 34 - line 42; figures -----	1
A	FR 2 581 569 A (OREAL) 14 November 1986 (1986-11-14) figures -----	1

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No

PCT/US 01/41306

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 3121906	A	25-02-1964	NONE	
JP 11221116	A	17-08-1999	NONE	
US 2118051	A	24-05-1938	NONE	
DE 7809143	U	06-07-1978	DE 7809143 U1	06-07-1978
EP 0315513	A	10-05-1989	FR 2622815 A1 EP 0315513 A1	12-05-1989 10-05-1989
FR 2581569	A	14-11-1986	FR 2581569 A1	14-11-1986

This Page Blank (uspio)